

80' RIGHT-OF-WAY

25' (TYP)
MAY VARY BASED ON DRAINAGE DESIGN

30' PAVEMENT WIDTH

5" PARABOLIC CROWN

CONCRETE CONTAINMENT STRIP

12" 18"

8" MINIMUM STABILIZED SUBGRADE IN ACCORDANCE WITH GEOTECHNICAL REPORT RECOMMENDATIONS (LIME OR CEMENT)

7" HOT MIX ASPHALTIC CONCRETE:
2" TYPE "D" H.M.A.C.
5" TYPE "A" OR TYPE "B" H.M.A.C. (2 LIFTS)


12" 18"

25' (TYP)
MAY VARY BASED ON DRAINAGE DESIGN

R.O.W. LINE

NOTES:

1. BAR DITCH SIDE SLOPE VARIES DEPENDING UPON DESIGN. NO GREATER THAN 3:1 WITHOUT AMORING.
2. GEOTECHNICAL REPORT (LIME SERIES TEST) PREPARED BY A LICENSED ENGINEER IS REQUIRED TO DETERMINE LIME OR CEMENT APPLICATION RATE.
3. MINIMUM LIME APPLICATION RATE SHALL BE 30 LBS./S.Y.
4. SUBGRADE COMPACTION SHALL BE 95% STANDARD PROCTOR DENSITY.



CONCRETE CONTAINMENT STRIP DETAIL

REINFORCING SHALL BE #4 BARS PLACED AS SHOWN.

P-04	RURAL RESIDENTIAL STREET (L2U) HMACH
CITY OF BURLESON	
ORIGINAL	10/6/06
REVISION	SWC
REVISION	
REVISION	